

#### CREATING A CLEANER, SAFER, HEALTHIER WORLD.



# **T20**

## HEAVY-DUTY INDUSTRIAL SCRUBBER

- Achieve excellent cleaning results with aggressive scrubbing and MaxPro<sup>2TM</sup> hydraulic technology
- Maximize productivity with ec-H2O<sup>TM</sup> technology for cleaning up to three times longer than conventional scrubbing
- Increase visibility with cab-forward design, open sightlines, and steering-wheel-mounted controls
- Improve the operator and supervisor experience with available Pro-Panel<sup>™</sup> technology

## A HIGH-PEFORMING, HEAVY-DUTY SCRUBBER FOCUSED ON DELIVERING CUSTOMIZED SOLUTIONS TO MEET CUSTOMER NEEDS



## THE T20 ADDRESSES YOUR KEY BUSINESS CHALLENGES

#### **REDUCE COST TO CLEAN**

\$

• Maximize productivity with an optional side brush that provides increased reach along edges and a wider cleaning path.

#### MAINTAIN HEALTH & SAFETY

• Ensure safe operation with cab-forward design that improves visibility and full front shroud that ensures operator leg and foot protection.

#### ENHANCE FACILITY IMAGE

• Deliver excellent cleaning results with MaxPro<sup>2TM</sup> hydraulic technology that provides consistent power to the brush drive motors regardless of floor surface changes.

#### EASY OPERATION & MAINTENANCE

• Reduce training and simplify operation with the Touch-n-Go<sup>™</sup> control module featuring 1-Step<sup>™</sup> start button.

## **INNOVATIVE** TECHNOLOGIES



### AVAILABLE PRO-PANEL<sup>™</sup> TECHNOLOGY REDEFINES THE USER EXPERIENCE

Transform your cleaning operation with Pro-Panel<sup>™</sup> technology – a revolutionary breakthrough in user experience. Pro-Panel<sup>™</sup> technology integrates multiple controls into an intuitive, high-visibility touch screen interface.

Effectively manage your asset and operators with supervisor controls that allow the machine function to be matched to the operator skill level and prevent unauthorized use.



- Ensure successful starts with **Pro-ID**<sup>TM</sup> operator login that automatically activates the specific operator's personalized cleaning settings and downloadable **Pro-Check**<sup>TM</sup> pre-operation checklists.
- Increase cleaning efficiency with programmable Zone Settings<sup>™</sup> that allow you to establish preferred cleaning settings by area of facility.
- Provide operators a view of their cleaning path without having to take their eyes off the direction of travel with **PerformanceView**<sup>TM</sup>.
- Increase visibility with backup camera featuring colored guidelines that help drivers avoid objects when in reverse.
- Reduce the need for extensive operator training with on-board, on-demand videos.
- Increase machine ease of use with **28 different language** options.

## ADDITIONAL EXCLUSIVE TECHNOLOGIES

All technologies increase scrub time up to three times using a single tank of water.



ec-H2O<sup>™</sup> technology electrically converts water into an innovative cleaning solution that cleans effectively, saves money, improves safety, and reduces environmental impact\* compared to daily cleaning floor chemicals and methods.





**ES® Extended Scrubbing** productivity enhancement system recycles cleaning chemicals to increase uptime and improve productivity by scrubbing floors using 66% less chemicals than traditional cleaning methods.

\* Based on a study by EcoForm<sup>™</sup>. Visit www.tennantco.com for more information.

## **INSIDE THE**



Touch-n-Go<sup>™</sup> control module ••• with 1-Step<sup>™</sup> start button allows easy access to cleaning settings without having to remove hands from wheel

> Full front shroud ensures operator leg and foot protection

Corrosion-resistant .... Duramer<sup>™</sup> construction on shrouding and solution and recovery tanks for long life

Front-wheel steering and high-traction tires provide excellent maneuverability in congested spaces Forward operating position improves operator safety and visibility

 Optional ec-H2O<sup>™</sup> technology improves productivity and reduces environmental impact

- · Solution and recovery tanks
- allow for complete visual
- inspection and cleanout

Heavy-gauge steel frame with full wraparound bumper and cushioned rollers help protect machine life

Yellow touch points save time and ensure proper maintenance

Cylindrical brushes and easy-to-remove debris tray maximize productivity

Dura-Track<sup>™</sup> parabolic squeegee with SmartRelease<sup>™</sup> improves water pickup and damage resistance

Scrubbing side brush widens cleaning path up to 54 in/1,370 mm.

Disk scrub head for effective scrubbing and simple no-tool brush change. Rear and side steel guards protect squeegee upon impact and prevent it from hooking on to obstacles.







## ENGINEERED FOR PRODUCTIVITY



Dura-Track<sup>™</sup> Parabolic Squeegee

- Touch-n-Go<sup>™</sup> control module with 1-Step<sup>™</sup> start button allows operators quick access to all settings without removing hands from the steering wheel.
- Cab-forward position and spacious operator compartment provide outstanding visibility, safety and ergonomics to protect operators, the machine and your facility.
- Dura-Track<sup>™</sup> parabolic squeegee with SmartRelease<sup>™</sup> delivers exceptional water pickup and reduces maintenance and replacement parts due to squeegee damage.
- Easy-access design offers quick service access and visibility to on-board diagnostics, helping minimize downtime and reduce maintenance costs.
- Debris tray on cylindrical units is equipped with handle and wheels to allow for simple and fast removal, transport, and emptying of the debris.
- Heavy-duty frame with cushioned corner rollers helps protect your facility and machine.



Easy-Access Design



**Debris Tray** 



Heavy-duty Frame and Cushioned Corner Rollers

Overhead guard protects operators from falling objects.

High-powered pressure washer allows for easy blast-cleaning of hard-to-reach areas.

Safety warning light ensures awareness of machine during operation.





#### TENNANT*TRUE®* PARTS, SERVICE AND FINANCE SOLUTIONS

- Reduce rework, labor and safety costs by using only Tennant*True* parts and service.
- Ensure optimal cleaning performance by selecting a Tennant*True* Service program provided by a network of over 400 factorytrained Tennant service representatives.
- Improve uptime by leveraging TennantTrue parts and service.
- Simplify budgeting by bundling Tennant*True* service plans, including parts, into the purchase or financing of your machine.



Manage your cleaning program with key performance metrics based on machine data.

Lease. Pre-Owned. Rent. Tennant has flexible options that get you the machines you need, however you need them.

#### T20 HEAVY-DUTY INDUSTRIAL SCRUBBER SCRUBBING SYSTEM

Cleaning path Cylindrical main brushes Disk main brushes With scrubbing side brush With sweeping side brush (cylindrical only)	40 in / 1,020 mm 42 in / 1,070 mm 54 in / 1,370 mm 56 in / 1,420 mm
BRUSH DRIVE SYSTEM	
Cylindrical main brushes Brush speed Brush down pressure (up to) Brush diameter (2) Disk main brushes Brush speed Brush down pressure (up to) Brush diameter (3) Disk side brush Brush speed	480 rpm 425 lb / 193 kg 12 in / 300 mm 230 rpm 400 lb / 181 kg 14 in / 360 mm
Scrubbing brush diameter Sweeping brush diameter (cylindrical)	16 in / 410 mm 21 in / 533 mm
SOLUTION DELIVERY SYSTEM	
Solution tank Solution capacity with ES <sup>*</sup>	80 gal / 303 L 125 gal / 473 L
RECOVERY SYSTEM	05 1/2/01
Recovery tank Demisting chamber Debris tray Volume capacity	95 gal / 360 L 15 gal / 57 L 1.1 ft³ / 31 L
Weight capacity Vacuum fans Speed	110 lb / 50 kg 11,000 rpm
Water lift	35 in / 890 mm
PROPELLING SYSTEM Propel speed forward (variable to) Propel speed reverse (variable to)	8.0 mph / 12.9 km/h 3.0 mph / 4.8 km/h
Engine-gasoline Gross Intermittent Power* Tennant Governed Power	50.7 hp / 37.8 kW @2800 rpm 40.6 hp / 30.3 kW @2300 rpm
Engine-LPG (2.0 L) Gross Intermittent Power* Tennant Governed Power Engine-diesel (1.5 L)	51.6 hp / 38.5 kW @2800 rpm 42.4 hp / 31.6 kW @2300 rpm
Gross Intermittent Power* Tennant Governed Power Gradeability	24.8 hp / 18.5 kW @2300 rpm 24.8 hp / 18.5 kW @2300 rpm
Transport at gross weight Working (cleaning) Ground clearance	10.0°/18% 8.0°/14% 3 in / 76 mm
MACHINE SPECIFICATIONS	
Length Width	95 in / 2,410 mm
Frame Rear squeegee With side brush	50 in / 1,270 mm 51 in / 1,300 mm 58 in / 1,473 mm
Height With overhead guard	58 in / 1,473 mm 83.5 in / 2,120 mm
Weight (empty)	3,300 lb / 1,497 kg
Minimum aisle turn	110 in / 2,790 mm
WARRANTY	
See your local representative for warranty information	).

See your local representative for warranty information.

\*Per SAE J1995 Specifications subject to change without notice.

> Tennant 701 North Lilac Drive Minneapolis, MN 55422 USA

USA/Canada: +1.800.553.8033 Quebec: +1.800.361.9050 Overseas: +1.763.540.1315

www.tennantco.com info@tennantco.com

SEEING IS BELIEVING

For a demonstration or additional information, call +1.800.553.8033 or email info@tennantco.com

t20-brochure-en-noam 4/2

©2020 The Tennant Company logo and other trademarks designated with the symbol "<sup>®</sup>" are trademarks of Tennant Company registered in the United States and/or other countries. Tennant Company's products are sold and serviced through subsidiaries of Tennant Company and distributors. All rights reserved.