

Basic Installation | Installation de base | Prosty montaż | Instalación básica | Basisinstallatie | Pose de base



Basic Installation (UK)

1. Clean floors with i-protect HDD and allow to dry thoroughly.
2. Position i-matt, press down leading edge to stick to floor, and roll out.
Note: Each roll consists of three pre-cut 91.5cm x 3m mats. i-matt can easily be trimmed with scissors or a utility knife to fit specific areas.
Note: When installing on tile floors, it's recommended that you do NOT follow the tile lines. Instead, position the edges of the mat at least 3cm from the grout line. This provides a better stick and helps prevent lifting.
3. Beginning at one end, press into place and smooth out with your hands, working from the centre to the edges. Press firmly for best adhesion, especially around the edges. You can walk on i-matt immediately, but leave down at least 24 hours before cleaning.
4. Leave in place. Treat i-matt as part of the floor and clean as you normally would using i-protect and i-mop. Do not lift or remove i-matt to clean underneath. When it's time to replace the mat, simply peel back a corner and pull it up. With i-matt, there will be no residue left behind.
Note: i-matt is extremely durable and designed to last up to 12 weeks. If the mat shows obvious signs of wear or a weakened bond to the floor before the end of that time frame, it should be replaced.

i-matt: i-matt is formulated to work with most common industrial and commercial floor surfaces but is not intended for home/residential use and wood flooring. All adhesive mats have some potential to leave residue or lift or discolour finish coatings, paint, and loose or predamaged tiles depending on the condition and age of the floor surface. If you have questions about the suitability of i-matt for your application, test a 15cm x 15cm piece in a noncritical area before use. i-matt should be replaced if it becomes saturated or shows signs of wear or damage.

CUSTOMER ASSUMES THE RISK THAT I-matt MAY DAMAGE OR ALTER CUSTOMER'S EXISTING FLOORING OR FLOOR COVERING. I-TEAM PROVIDES NO WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE AND NO WARRANTY THAT THE USE OF AN ADHESIVE-BACKED MAT WILL BE ACCEPTABLE FOR USE IN THE CUSTOMER'S FACILITY. I-TEAM SHALL HAVE NO RESPONSIBILITY FOR, AND CUSTOMER HEREBY RELEASES AND DISCHARGES I-TEAM FROM, ANY DIRECT, INDIRECT, INCIDENTAL OR CONSEQUENTIAL DAMAGES TO CUSTOMER'S FLOORS, FLOORING MATERIAL, OR ANY OTHER SURFACES IN CUSTOMER'S FACILITY. CUSTOMER IS SOLELY RESPONSIBLE FOR DETERMINING THE FITNESS AND APPROPRIATENESS OF THE USE OF AN I-matt IN CUSTOMER'S FACILITY.